

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 3352

Latitude 37°30' Longitude 119°30'

- (7) FROM POINT 6 MILES WEST OF HAPPY ISLES BRIDGE ALONG PARK
ROADS SOUTH AND SOUTHEAST THROUGH WAWONA AND SOUTH ENTRANCE
INTO BASS LAKE QUADRANGLE (418)

Wawona-Old Village Rd. junction, 1.0 mi. SW. of, 46 ft. S. of
center of Wawona Rd., 100 ft. E. of deep, steep drain that
intersects rd. at right angles, 5 ft. W. of 30 inch lone cedar
tree, about 6 ft. above rd. level, in 1 1/2 inch galvanized
iron pipe; top of copper nail

4239.143

Wawona-Old Village Rd. junction, 1.65 mi. SW. of, at Wawona
tunnel, 8 ft. E. of E. portal and in line with N. wall of
tunnel, cemented in E. end of N. curb to tunnel drain;
standard tablet stamped "30 B 1934 4409" (USC&GS 37119-4-104)

NEW DESC

4409.233

Reference mark, 120 ft. N. of tablet, 35 ft. E. of W. end
and 3 inches N. of stone retaining wall, in 1 1/2 inch
galvanized iron pipe; top of copper nail.

4406.200

Wawona -Old Village Rd. junction, 2.5 mi. SW. of, at Wawona
tunnel, 4 ft. W. of W. portal and in line with N. wall of
tunnel, cemented in W. end of N. curb to tunnel drain; stan-
dard tablet stamped "31 B 1934 4621" (USC&GS 37119-4-104)

NEW DESC.

4621.631

Reference mark, 75 ft. NW. of tablet, 6 inches NE. of large
granite boulder, in 1 1/2 inch galvanized iron pipe; top of
copper nail

4621.792

Wawona-Old Village Rd. junction, 2.8 mi. SW. of, 0.25 mi. W.
of W. portal of Wawona tunnel, 33 ft. NW. of center of rd. at
small turnout, top of rock, U.S. Dept. of Agriculture, Bureau
of Public Roads B.M. stamped "139 + 70.91" "4697.01 1932"

4697.459

Wawona-Old Village Rd. junction, 3.3 mi. SW. of, in approximate
line and W. of long eastern tangent of a stone retaining wall,
22 ft. SW. of center of rd., 45 ft. W. of 18 inch galvanized
iron culvert, top of rock outcrop; Bureau of Public Roads BM
stamped "165 + 78.84, 4830.50 1932"

SENF 86

4830.889

Wawona-Old Village Rd. junction, 3.4 mi. SW. of, 200 ft. E. of
W. end of stone retaining wall, 25 ft. N. of center of rd., top
of retaining wall; Bureau of Public Rds. BM stamped "176 + 20.06,
1317 + 42.21, 4871.91 1932"

DESTROYED

4872.444

cl

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

- (7) Wawona-Old Village Rd. junction, 3.9 mi. SW. of, at top of small rise, 23 ft. W. of center of rd., 110 ft. N. of lone dead cedar tree, 320 ft. N. of small drain and dim rd. forks to NE., top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "1290 + 38.50, 5002.60 1932" *SFNF86* 4923.573
- Reference mark, 380 ft. SE. of bench mark, B.P.R. tablet stamped "1289 + 50.27" 4920.041
- Wawona-Old Village Rd. junction, 4.7 mi. SW. of, at rock bluff overlooking canyon, about 230 ft. S. of elevation 5000 signpost, 30 ft. W. of center of rd., 24 ft. N. of galvanized iron culvert, top of 2 inch galvanized iron pipe cemented in rock; Bureau of Public Rds. BM stamped "1254 + 48.25, 5046.80 1932" *NEW DESC. 8* 4967.880
- Ref. mark, 44 ft. S. of tablet; top of rock; chiseled square 4968.554
- Wawona-Old Village Rd. junction, 5.1 mi. SW. of, 27 ft. W. of center of rd. on outside of curve, just S. of two large pine trees, 165 ft. SW. of lone dead tree on opposite side of rd., top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "1233 + 16.62, 1233 + 10.17 5138.97 1932" *SFNF86* 5059.56 961
- Wawona-Old Village Rd. junction, 5.4 mi. SW. of, 51 ft. W. of center of rd. on outside curve, 90 ft. S. of large pine tree, 33 ft. NW. of small cedar tree, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "1217 + 45.32, 5122.90 1932" 5043.867
- Wawona-Old Village Rd. junction, 5.5 mi. SW. of, 26 ft. W. of center of rd., at cut, 210 ft. S. of culvert, 5 ft. N. of large partially embedded granite boulder, 4 ft. SE. of 36 inch cedar tree, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "1213 + 01.52, 5130.81 1932" *DESTROYED* 5051.793
- Wawona-Old Village Rd. junction, 5.9 mi. SW. of, 3.7 mi. N. of Chinquapin, at Grouse Creek, 170 ft. N. of creek, 26 ft. E. of center of rd., 15 ft. E. of guardrail and 27 ft. S. of N. end of guardrail, top of rock; standard tablet stamped "32 B 1934 5110" (USC&GS 37119-4-104) *NEW DESC. 8* 5110.679
- Reference mark, 94 ft. S. of tablet, 9 ft. E. of 36 inch cedar tree, 20 ft. E. of stump, in 1 1/2 inch galvanized iron pipe; top of copper nail 5104.373

cl

YOSEMITE (437)

California

C. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

(7)

Chinquapin, 3.5 mi. N. of, about 700 ft. W. of Grouse
Creek, 23 ft. NW. of center of rd., 16 ft. SE. of large
dead pine tree, NE. of turnout at cut, about 7 ft. above rd.
level, top of 2 inch galvanized iron pipe; Bureau of
Public Rds. BM stamped "1177 + 18.34, 5238.13 1932"

SFNF86
5159.167

Chinquapin, 3.0 mi. N. of, 45 ft. NW. of center of rd., at
turnout where rd. curves from W. to S., 20 ft. SW. of two
large pine trees with broken tops, 75 ft. E. of broken
top fir tree, top of 2 inch galvanized iron post; Bureau
of Public Rds. BM stamped "1154 + 20.70, 1154 + 17.46,
5372.92 1932"

SFNF86
5293.910

Chinquapin, 2.6 mi. N. of, 22 ft. E. of center of rd., 17
ft. W. of 60 inch cedar tree, 40 ft. S. of culvert, 5.5
ft. E. of stump, about 3 ft. above rd. level, top of 2
inch galvanized iron pipe; Bureau of Public Rds. BM
stamped "1129 + 17.50 5471.65 1932"

SFNF86
5404.660

Chinquapin, 2.5 mi. N. of, 450 ft. SE. of B.P.R.B.M.
"1129 + 17.50", on opposite side of rd., 6 ft. E. of large
granite boulder, 22 ft. W. of 60 inch pine tree, 5 ft. below
rd. level, top of 2 inch galvanized iron pipe; Bureau of
Public Rds. BM stamped "1127 + 95.35 5489.70 1932"

SFNF86
5422.662

Chinquapin, 2.1 mi. N. of, 33 ft. E. of center of rd., 31
ft. W. of culvert, W. of clump of small pines, 110 ft. SE.
of turnout and about 5 ft. above rd. level, top of 2 inch
galvanized iron pipe; Bureau of Public Rds., BM stamped
"1105 + 40.82 5594.94 1932"

SFNF86
5515.793

Chinquapin, 2.0 mi. N. of, 750 ft. SW. of B.P.R.B.M.
"1105 + 40.82", 32 ft. SE. of center of rd., 50 ft. S. of
culvert, at clump of small pines in drain, E. and on
opposite side of rd., at large dead pine, top of 2 inch
galvanized iron pipe; Bureau of Public Rds. BM stamped
"1101 + 50.17, 5624.24 1932"

SFNF86
5545.025

Chinquapin, 1.7 mi. N. of, 640 ft. S. of Avalanche Creek,
35 ft. SW. of center of rd., top of large prominent boulder
at E. edge of turnout; standard tablet stamped "33 B 1934
5599"

NEW DESC.
5599.615

Reference mark, 450 ft. N. of tablet, 185 ft. S. of
Avalanche Creek, 37 ft. W. of center of rd., at edge of
turnout, top of 2 inch galvanized iron pipe; Bureau of Public
Rds. BM stamped "1087 + 66.69, 5663.28 1932"

SFNF86
5584.061

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

- (7) Chinquapin, 1.4 mi. N. of, 37 ft. W. of center of rd. on outside of curve, 6.5 ft. W. of stump located on bank of curve, 11 ft. SE. of 24 inch cedar tree, 17 ft. NE. of 24 inch fir tree, about 2 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "1070 + 42.78, 5748.19 1932" *SFNF86*
5669.001
- Chinquapin, 0.7 mi. N. of, 24 ft. W. of center of rd., 19 ft. SE. of an 84 inch yellow pine, 110 ft. N. of broken top fir tree, 215 ft. S. of culvert, about 4 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "1033 + 59.14, 5930.78 1932" *SFNF86*
5851.593
- Chinquapin, 0.7 mi. N. of, 320 ft. SE. of B.P.R. "1033 + 59.14 5930.78", on opposite side of rd., about 3 ft. above rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "1033 + 59.14, 5954.02 1932" *SFNF86*
5874.831
- Chinquapin, 0.25 mi. N. of, 60 ft. S. of small creek, 20 ft. NE. of center of rd. where turns from E. to S., 21 ft. S. of 84 inch fir tree, at toe of painted rock, about 2 ft. above rd. level, set flush with ground, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "1010 + 35.90, 6063.91 1932" *SFNF86*
5984.739
- Chinquapin, on front steps of Chinquapin Ranger Station, 65 ft. W. of center of rd., 50 ft. W. of flag pole, 6 inches from S. end and 8 inches from E. edge of first step; standard tablet stamped "34 B 1934 6039" (USC&GS 37119-4-104) *NEW DESC.*
6039.906
- Reference mark, 150 ft. NE. of tablet, 30 ft. NW. of center of rd. and about 4 ft. below rd. level, in 1 1/2 inch galvanized iron pipe; top of copper nail
6034.964
- Chinquapin, 0.3 mi. S. of, 23 ft. E. of center of rd., 6 ft. SE. of prominent 60 inch fir tree at E. edge of rd., 5 ft. E. of stump, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "980 + 68.30, 6167.02 1932" *DISTURBE*
6087.799
- Chinquapin, 0.5 mi. S. of, at summit, 31 ft. SW. of center of rd., 200 ft. S. of rd. forks to W., 130 ft. NE. of fire motorway, 2.5 ft. N. of post, top of rock; standard tablet stamped "35 B 1934 6124" *SFNF86*
6124.085

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

- (7) Reference mark, 140 ft. N. of tablet, 40 ft. W. of center of rd., 60 ft. S. of rd. forks to W., about 8 ft. above rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "974 + 99.53, 6209.43 1932" *SFNF86*
6130.230
- Chinquapin, 0.9 mi. S. of, 38 ft. E. of center of rd., 18 ft. N. of small drain, 21 ft. NE. of culvert, 21 ft. S. of 60 inch cedar tree, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "953 + 25.60, 6086.62 1932" 6007.480
- Chinquapin, 1.2 mi. S. of, 200 ft. NW. of a group of dead pine trees on opposite side of rd., 125 ft. S. of 84 inch leaning cedar tree, 38 ft. W. of center of rd., 9 ft. SE. of 30 inch live oak tree, about 8 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "942 + 57.87, 6010.93 1932" 5931.826
- Chinquapin, 1.4 mi. S. of, 82 ft. S. and 25 ft. W. of drain, 60 ft. W. of center of rd., at deep fill, 40 ft. NE. of culvert, 34 ft. SE. of 60 inch burnt yellow pine tree, 18 inches N. of arrow pointed rock, set flush with ground; Bureau of Public Rds. BM stamped "929 + 40.73 1932" *SFNF86*
5875.554
- Chinquapin, 1.4 mi. S. of, 300 ft. NW. of B.P.R.B.M., "929 + 40.73" (same station stamping), 22 ft. W. of center of rd., at cut, 24 ft. SE. of 48 inch burnt cedar tree, set flush with ground; Bureau of Public Rds. BM stamped "929 + 40.73, 5973.76 1932" *SFNF86*
5894.568
- Chinquapin, 2.0 mi. S. of, at Rail Meadows Creek, 90 ft. SE. of creek crossing, 43 ft. E. of center of rd., 23 ft. above rd. level, 5 ft. SW. of 6 inch pine tree, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "899 + 68.50 1932" *QUESTION*
5769.845
- Chinquapin, 2.1 mi. S. of, 630 ft. S. of B.P.R.B.M. "899 + 68.50", 24 ft. W. of center of rd., 15 ft. SE. of quadruplet live oak tree, 11 ft. N. of stump, about 3 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "895 + 19.21, 5800.65 1932" *SFNF86*
5721.644
- Chinquapin, 2.5 mi. S. of, at Strawberry Creek, 100 ft. N. of creek, 30 ft. SW. of center of rd., at curve in rd. from E. to S., top of large lone prominent boulder; standard tablet stamped "36 B 1934 5626" *SFNF86*
5626.856

FINAL COPY

cl

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

- (7) Reference mark, 150 ft. SE. of tablet, on opposite side of creek and rd., 35 ft. E. of center of rd. about 12 ft. above rd. level, top of $\frac{1}{2}$ inch galvanized iron pipe; Bureau of Public Rds. BM stamped "874 + 40.00 1932" *NEW DESC. 8*
5636.922
- Chinquapin, 2.6 mi. S. of, about 700 ft. S. of B.P.R.B.M. "874 + 40.00" and on opposite side of rd., top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "873 + 10.08, 5671.95 1932" 5592.966
- Chinquapin, 3.0 mi. S. of, 30 ft. SW. of rd., at curve, 60 ft. N. of large granite boulders, 11 ft. E. of 54 inch yellow pine, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "849 + 89.40 1932" *SFNF 86*
5558.758
- Chinquapin, 3.0 mi. S. of, 310 ft. SE. of B.P.R.B.M. "849 + 89.40", top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "847 + 95.28 1932" *SFNF 86*
5544.895
- Chinquapin, 3.3 mi. S. of, 650 ft. N. of rd. forks to NW. 30 ft. SE. of center of rd., on outside of curve, 20 ft. S. of 84 inch cedar tree, 70 ft. NE. of 2 large fir trees, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "832 + 49.10" *QUESTIONAB*
5522.273 *86*
- Chinquapin, 4.1 mi. S. of, at Bishop Creek, 70 ft. SW. of center of rd., about 200 ft. N. of Bishop Creek, 500 ft. W. of where rd. crosses creek, 50 ft. S. of 2 pine trees among group of granite boulders, top of boulder overlooking creek; standard tablet stamped "37 B 1934 5501" (USC&GS 37119-4-104) 5501.242
- Reference mark, 26 ft. W. of tablet, 32 ft. SE. of 2 pine trees and about 8 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "790 + 54.22" *SFNF 86*
5497.974
- Chinquapin, 4.5 mi. S. of, 34 ft. SW. of center of rd. on outside of curve from SE. to E. at cut around toe of ridge, 13 ft. N. of 50 inch pine tree, 10 ft. N. of 36 inch cedar tree burnt at base, 37 ft. W. of 84 inch pine tree, 5 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "769 + 27.94" *QUESTION*
5500.706
- Chinquapin, 4.5 mi. S. of, 360 ft. E. of B.P.R.B.M. "769 + 27.94", 80 ft. E. of stone headwall of culvert; Bureau of Public Rds. BM stamped "768 + 63.52" *SFNF 86*
5510.948 *cl*

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

- (7) Chinquapin, 5.1 mi. S. of, 330 ft. SE. of highway turnout to stock pile, 105 ft. S. of small drain, 45 ft. E. of rd., 7 ft. S. of 60 inch fir tree, 8 ft. N. of 42 inch dead fir tree, about 15 ft. above rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "739 + 90.30" *SFNF86*
5456.759
- Chinquapin, 5.2 mi. S. of, 650 ft. S. of B.P.R.B.M. "739 + 90.30", top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "737 + 47.06" *SFNF86*
5452.695
- Chinquapin, 5.5 mi. S. of, 62 ft. NE. of center of rd. where rd. turns from E. of S., 60 ft. SE. of drain and culvert, 55 ft. N. of large granite boulder at edge of rd., 20 ft. N. of 60 inch live oak tree, about 3 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "720 + 25.71" *SFNF86*
5410.721
- Chinquapin, 5.5 mi. S. of, 260 ft. W. of B.P.R.B.M. "720 + 25.71" (same stamping) *SFNF86*
5422.738
- Chinquapin, 5.8 mi. S. of, 0.25 mi. in a southerly direction from B.P.R.B.M. "720 + 25.71", 23 ft. E. of center of rd., 95 ft. N. of galvanized iron culvert, 45 ft. NE. and on opposite side of rd. from a 60 inch cedar tree that leans over rd., 47 ft. S. of 42 inch cedar tree, 13 ft. SW. of dead tree, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "704 + 89.36" *SFNF86*
5395.219
- Reference mark, 320 ft. SW. of B.P.R.B.M. "704 + 89.36", B.P.R.B.M. stamped "704 + 40.38" *SFNF86*
5381.054
- Chinquapin, 6.2 mi. S. of, at small drain, 55 ft. N. of culvert, 26 ft. E. of center of rd., 12 ft. NE. of 36 inch live oak at W. edge of a group of small cedar trees, about 3 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "687 + 36.88" *SFNF86*
5297.461
5305.945 - *SF*
- Ref. Mark 220 ft. NW. of tablet; BPR BM stamped "687+36.88"
Chinquapin, 6.5 mi. S. of, 50 ft. NW. of center of rd. at S. curve through small cut, 80 ft. N. of a 78 inch lone pine tree, about 100 ft. S. of 3 cedar trees, 125 ft. SW. and on opposite side of rd., from a large knobbed pine tree, 180 ft. S. of galvanized iron culvert, top of highest boulder; standard tablet stamped "38 B 1934 5232" *SF*
5232.779

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

- (7) Reference mark, 320 ft. N. of tablet, 50 ft. SW. of center of rd., 5 ft. E. of 54 inch cedar tree, in S. root of a 66 inch pine tree burnt on the E. side; top of nail, lath tacked on tree marked "BM 5320.53" 5241.383
- Chinquapin, 7.0 mi. S. of, 140 ft. S. of large lone pine tree, 31 ft. SW. of center of rd., at curve and just S. of turnout, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "642 + 98.25, 1934" *SFNFB* 5089.427
- Chinquapin, 7.0 mi. S. of, 360 ft. SE. of B.P.R.B.M. "642 + 98.25", and on opposite side of rd., top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "642 + 00.06, 1934" *SFNFB* 5077.161
- Chinquapin, 7.8 mi. S. of, 4.8 mi. N. of Hotel Wawona, 275 ft. S. of Alder Creek crossing, 90 ft. N. of a 66 inch leaning pine tree, 15 ft. W. of center of rd., top of highest boulder in place; standard tablet stamped "39 B 1934 4887" (USC&GS 37119-4-104) 4887.910
- Reference mark, 400 ft. S. of tablet, 16 ft. W. of center of rd., 10 ft. SE. of prominent rock outcrop, top of a 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "599 + 59.99" *SFNFB* 4862.138
- Hotel Wawona, 4.4 mi. N. of, 400 ft. W. of picnic grounds, 75 ft. SW. of small creek, 55 ft. N. of center of rd., 10 ft. W. of two cedar trees, about 8 ft. below rd. level and among group of small fir trees, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "580 + 31.11, 580 + 32.07" *NEW DESC.* 4765.004
- Hotel Wawona, 3.6 mi. N. of, 50 ft. S. of dirt trail to NW. and small drain, 40 ft. E. of center of rd., 24 ft. N. of 30 inch live oak tree, 12 ft. above rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "538 + 06.83" *SFNFB* 4589.671
- Hotel Wawona, 3.5 mi. N. of, 400 ft. SW. of B.P.R.B.M. "538 + 06.83", 23 ft. W. of center of rd., 19 ft. S. of embedded boulder, S. of turnout, 15 ft. N. of 36 inch live oak tree, 3 ft. N. of 30 inch live oak tree, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "537 + 52.15" *SFNFB* 4561.297

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

- (7) Hotel Wawona, 2.5 mi. N. of, 650 ft. S. of drain, 185 ft. NW. of an 18 inch galvanized iron culvert, 80 ft. S. of S. end of stone retaining wall, 30 ft. W. of center of rd., S. of turnout at large side hill cut, top of quartzite rock; standard tablet stamped "40 B 1934 4313" (USC&GS 37119-4-104) 4313.138
- Reference mark, about 1100 ft. S. of tablet, 235 ft. S. of galvanized iron culvert, 220 ft. S. of large lone pine tree, 26 ft. W. of center of rd., 20 ft. S of double live oak tree, about 2 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "464 + 77.81" SFNF86 4239.150
- Hotel Wawona, 1.7 mi. N. of, 23 ft. W. of center of rd. on outside of curve, 15 ft. NE. of 2 large pine trees, 2 ft. SE. of 24 inch pine tree among filled-in granite boulders, about 2 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "433 + 64.07 P.I." SFNF86 4065.110
- Hotel Wawona, 1.4 mi. N. of, 220 ft. SE. of rd. forks to NW., 30 ft. N. of granite boulder with leaning live oak tree growing out of it, 27 ft. SW. of center of rd., 2 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "411 + 85.64 411 + 86.37" SFNF86 3954.579
- Wawona P.O. in Mariposa County, 0.9 mi. N. of, along the Yosemite Valley Rd.; about 350 ft. S. of the driveway into the Wawona Campground, 45 ft. S. of a 42-inch live oak tree, 35 ft. W. of the centerline of the rd.; in the top of a granite boulder; standard tablet stamped "3926 41 B 1934" (USC&GS 37119-4-104) NEW DEK 3927.138
- Reference mark, 270 ft. S. of tablet, 80 ft. E. of S. fork of Merced River, 70 ft. S. of S. driveway to A.E. Wood Camp, 40 ft. S. of 34 inch pine tree, 21 ft. W. of center of rd., top of 1-1/2 inch galvanized iron pipe; nail inscribed "102" (Yosemite National Park Traverse Station) SFNF86 3922.994
- Reference mark No. 2, 420 ft. S. of tablet, 28 ft. SW. of center of rd., 10 ft. SE. of 24 inch pine tree, 8 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "42 231 + 28, 3990.84 1931" SFNF86 3912.806
- Hotel Wawona, 0.7 mi. N. of, Yosemite National Park Traverse Station, 280 ft. N. of B.P.R.B.M. "40, 296 + 18", 18 ft. W. of center of rd., at edge, 8 ft. E. of 24 inch cedar tree, top of 2 inch galvanized iron pipe; nail, inscribed "101" SFNF86 3936.885

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

(7)

Hotel Wawona, 0.7 mi. N. of, 110 ft. SW. of large forked pine,
70 ft. E. of S. fork of Merced River where rd. leaves river,
62 ft. SW. of center of rd., top of 2 inch galvanized iron pipe;
Bureau of Public Rds. BM stamped "40 296 + 18, 4010.56 1931"

SFNF86
3932.653

Hotel Wawona, 0.35 mi. N. of, 300 ft. N. of S. fork of Merced
River, 60 ft. NE. of center of rd., 7 ft. S. of two pines, top
of 2 inch galvanized iron pipe; Bureau of Public Rds. BM
stamped "39 266 + 51 4033.89 1931"

SFNF8
3955.821

Hotel Wawona, at, 30 ft. W. of steps to front entrance, 75 ft.
E. of fountain, 8 inches E. of center of W. light post,
cemented in walk; standard tablet stamped "42 B 1934 4012"
(USC&GS 37119-4-104)

4011.937

Reference mark, 63 ft. W. of tablet, on SW. edge of walk to
Club house, 75 ft. SE. of Club house; top of iron disk
cemented in walk (Note: This disk is the sec cor. between
secs. 2 & 3)

4009.607

Hotel Wawona, 0.7 mi. SE. of, 35 ft. W. of center of rd. at
small cut, 15 ft. S. of 60 inch lone prominent pine, top of
2 inch galvanized iron pipe; Bureau of Public Rds. BM
stamped "33, 215 + 35, 4236.35 1931"

SFNF8
4158.393

Hotel Wawona, 0.9 mi. SE. of, 50 ft. SE. of culvert, 36 ft. NW.
of centerline of rd., 10 ft. NE. of 36 inch live oak tree, on
opposite side of rd. from a large lone pine, 9 ft. SE. of 36
inch live oak tree, about 7 ft. above rd. level, top of 2 inch
galvanized iron pipe; Bureau of Public Rds. BM stamped "32
4298.99 1931"

SFNF8
4221.075

Hotel Wawona, 1.2 mi. SE. of, 68 ft. S. of culvert, 30 ft. SW.
of center of rd., 24 ft. N. of a 40 inch live oak, 19 ft. NW.
of a 42 inch pine, 9 ft. W. of two live oaks, about 4 ft. below
rd. level, top of 2 inch galvanized iron pipe; Bureau of Public
Rds. BM stamped "30, 29 + 80 4375.22 1931"

SFNF8
4297.388

Hotel Wawona, 1.4 mi. SE. of, 75 ft. SE. of small drain, 70 ft.
NE. of center of rd., 65 ft. NW. of live oak tree, 39 ft. E. of
two large granite boulders, about 15 ft. above rd. level, top of
2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped
"29 67 + 49 4448.43 1931" (Not found)

4370.593

Yosemite (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5352

- (7) Hotel Wawona, 1.6 mi. SE. of, 110 ft. SE. of dim rd. forks to NE., 100 ft. SE. and on opposite side of rd., from a lone cedar tree, 66 ft. E. of culvert, 21 ft. S. of center of rd., at curve, 4 ft. SE. of 30 inch pine, just E. of a group of pines, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "27 129 + 03 4520.22, 1931" (Not found) *SFNFB* 4442.39
- Hotel Wawona, 1.6 mi. SE. of, 25 ft. W. of B.P.R.B.M. "27, 129 + 03", in E. root of pine tree; nail, lath tacked on tree marked "BM 24 4514.42" 4436.42
- Hotel Wawona, 1.7 mi. SE. of, 750 ft. E. of B.P.R.B.M. "27, 129 + 03", 80 ft. W. of center of rd., 5 ft. W. of burnt cedar tree, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "26, 343 + 65 4565.93 1931" (Not found) *SFNFB* 4488.04
- Hotel Wawona, 1.9 mi. SE. of, 130 ft. NW. of trail crossing, 65 ft. NW. of 36 inch pine tree, 40 ft. NW. of center of rd. where rd. curves from NE. of SE., 36 ft. SW. of two cedar trees side by side, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "25 166 + 15, 4613.62 1931" (Not found) 4535.68
- Hotel Wawona, 2.2 mi. SE. of, 1400 ft. E. of B.P.R.B.M. "25 166 + 15", 95 ft. E. of culvert, 70 ft. E. of 40 inch cedar tree, 37 ft. E. of live oak tree, 36 ft. W. of center of rd., about 5 ft. above rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "24 213 + 55, 4694.50 1931" 4616.603
- Hotel Wawona, 2.5 mi. SE. of and 2.2 mi. N. of S. entrance, 145 ft. SE. of a lone pine and lone live oak, on opposite side of rd., 39 ft. N. of cut and NW. of where rd. turns from SE. to SW., 36 ft. NE. of rd., about 4 ft. above rd. level, top of W. boulder of three boulders; standard tablet stamped "43 B 1934 4693" 4692.972
- Reference mark, 15 ft. S. of tablet, top of rock; chiseled square 4690.382
- Yosemite National Park, 1.9 mi. N. of S. entrance, 165 ft. W. of fill terraced with pine poles, 145 ft. W. of a group of pines, 45 ft. W. of center of rd. and about 3/4th of the way up the side of a cut, about 16 ft. above rd. level, top of 3 inch pipe (boundary post) projecting about 12 inches above ground stamped "NO. 166 1906" 4747.854

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: B 5353

- (7) Yosemite National Park, 1.6 mi. N. of S. entrance, 105 ft. SW. from a 72 inch pine tree, 37 ft. N. of center of rd., at cut where rd. curves from NW to SW., 34 ft. E. of a 54 inch pine, about 9 ft. above rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "21, 160 + 65, 4847.91 1931" (Not found) 4769.910
- Yosemite National Park, 1.3 mi. N. of S. entrance, 32 ft. NW. of center of rd., SW. of cut where rd. curves from W. to S., 30 ft. E. of a 66 inch pine tree, 8 ft. S. of an imbedded granite boulder, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "19 113 + 45, 4879.11 1931" (Not found) SFNF8 4801.431
- Yosemite National Park, 1.1 mi. N. of S. entrance, 90 ft. E. of lone cedar tree, top of small cut, 40 ft. SW. of 72 inch cedar tree, 30 ft. N. of center of rd., about 3 ft. above rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "17 247 + 30, 4956.28, 1931" (Not found) 4878.431
- Reference mark, 1150 ft. SW. of B.P.R.B.M., "17 247 + 30", 105 ft. SW. of large fir tree, 40 ft. SW. of a cedar tree, 30 ft. NW. of rd., about 5 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "16, 38 + 85, 5008.98 1931" SFNF8 4931.094
- Yosemite National Park, 0.6 mi. N. of S. entrance, 95 ft. S. of two small live oaks, 40 ft. E. of rd. where rd. turns from W. to S., overlooking valley, 30 ft. SE. of culvert, about 10 ft. above rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "15, 63 + 10, 5095.17 1931" 5017.253
- Reference mark, 1150 ft. S. of B.P.R.B.M., "15 63 + 10", at S. end of long tangent, 40 ft. SW. of center of rd., top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "13 163 + 65 5139.87 1931" SFNF8 5062.142
- Yosemite National Park, 600 ft. W. of S. entrance, 38 ft. S. of center of rd., just W. of top of hill, 54 ft. SE. of "SLOW RANGER STATION 200 YDS" sign, about 3 ft. below rd. level, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "12 177 + 85 5195.97 1931" (Not found) SFNF8 5118.075

YOSEMITE (437)

California

G. Brumund, 1934

Third Order

Adjusted Elevations Based
On Sea Level Datum of 1929

Book: Books: B 5353 & 5354

- (7) Yosemite National Park, S. entrance, 270 ft. NW. of checking station and rd. junction to Fresno, 35 ft. W. of center of rd., 150 ft. W. of driveway, 60 ft. W. of Rangers' tent, 15 ft. W. of small pine tree, 10 ft. E. of small pine and about 6 ft. above rd. level, top of concrete post; standard tablet stamped "44 B 1934 5130" (USC&GS 37119-4-104)

5130.285

Reference mark, 20 ft. NE. of tablet, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "12 520 + 8.69 1414 + 37.64 247.37 1931"

SFNF&
5130.708

Yosemite National Park, 0.3 mi. S. of S. entrance, 235 ft. S. of drain and on edge of small cut, 35 ft. W. of center of rd., 30 ft. E. of two cedar trees, top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "10 5147.89 130 + 00 28.51 1931" (Not found)

SFNF&
5070.022

Reference mark, 760 ft. S. of B.P.R.B.M., "10 130 + 00 28.51, 270 ft. S. of small drain, 35 ft. W. of center of rd., top of 2 inch galvanized iron pipe; Bureau of Public Rds. BM stamped "9 5136.64 122 + 06.34 28.51 1931"

5058.772

South Entrance, 0.6 mi. S. of, 850 ft. W. of BM "60 B 1934", 70 ft. NE. of rd. at curve in rd. from SE. to S.; on top of a 2 inch galvanized iron pipe; a B.P.R.B.M. stamped "8 5117.51 111+25.30 200.51 1931"

SFNF&
5039.747